

Clean room luminaire/recessed luminaire - Satin-finished diffuser - direct distribution

Sheet steel housing suitable for ceilings with visible T-rails, concealed symmetrical rail constructions and cut-out ceilings; the protection rating refers to the visible luminaire surface; suitable for use in clean rooms and clean room areas per DIN 14644-1; manufactured per IPA provisions, as well as the directives for quality assurance GMP (Good Manufacturing Practice); Housing colour traffic white RAL 9016; Direct diffuse light distribution using acrylic satin-finish diffuser with naturally anodised aluminium frame, neutral white light colour (840) with very good colour consistency and high colour rendering  $R_a > 80$ ; Integrated LED driver design. Electrical connection and connection of control cable using 5-pole connection terminal with plug-in contacts; With changeover converter for emergency lighting operation on request. UBM universal fastening mechanism for concealed symmetrical rail constructions included in delivery. An extractor is included for prismatic and frosted panes to remove the sealing frame. UBM universal fastening mechanism for concealed symmetrical rail constructions included in delivery. Suitable for air purity class ISO 14644-1 Class 2 with excellent to very good results in terms of microbial metabolic potential and chemical resistance.

CHARACTERISTICS

|                               |  |
|-------------------------------|--|
| Order number                  | 72512036613  |
| EAN number                    | 4020863330553  |
| Commodity code                | 94051190   |
| Certification mark            | IP 54, Protection class I, F, IPA, Clean room, HACCP DIN10500/Food/IFS/BRC, Indoor, CE |
| Impact resistance (IK rating) | IK03   |
| Ambient temperatur            | ta 25°C  |
| Special properties            | Ready for IoT  |
| Warranty period               | 5 years  |
| State funding programs        | BEG - Federal funding for efficient buildings (valid only for Germany)                 |

ELECTRICAL ENGINEERING


|                                      |  |
|--------------------------------------|--|
| Controller                           | Electronic driver DALI2 (1 pcs.)                           |
| System output                        | 29W  |
| Mains voltage                        | 230V/50Hz  |
| Circuit breakers (inrush current)    | 13 pieces/B10, 21 pieces/B16, 21 pieces/C10, 35 pieces/C16 |
| Energy efficiency class/light source | C  |

LIGHTING TECHNOLOGY


|                                    |  |
|------------------------------------|--|
| Placement                          | LED, Colour rendering/Light colour CRI $\geq 80$ / 4000K |
| Colour tolerance (MacAdam)         | 3SDCM  |
| Photobiological safety (Luminaire) | RG0  |
| Nominal luminous flux              | 4839lm   |
| LED service life                   | 50000h L80/B10 (Tq 25°C)                                 |
| Luminaire luminous efficiency      | 169lm/W  |
| UGR lat./long.                     | 20.9 / 21.4  |

DEEP-LINK

<https://www.regiolux.de/en/article/72512036613>



|                              |                |
|------------------------------|----------------|
| Reference                    | LED 4700lm 840 |
| $\eta_{LB}$                  | 100 %          |
| $\Phi_{\downarrow}/\uparrow$ | 100 % / 0 %    |
| UGR lat./long.               | 20.9 / 21.4    |



MECHANICS

|                         |   |
|-------------------------|---|
| Housing colour          | traffic white RAL 9016  |
| Dimensions (LxWxH/DxH)  | 1247mm x 309mm x 89mm   |
| Depth                   | 82mm  |
| Ceiling system          | ceilings with visible T-rails [s-TS] (312.5x1250 mm), Concealed symmetrical rail construction [VS] (312.5x1250 mm), cut-out ceilings [AD] |
| Ceiling cut-out (LxW/D) | 1185mm x 285mm  |
| Installation depth      | 150mm [AD]; 250mm [s-TS]; 150mm [s-TS] min; 150mm [VS]  |
| Weight (net)            | 6.71kg  |
| Type of installation    | Installation in clean room ceilings, Ceiling installation individual mounting   |

Dimensions

|          |          |   |
|----------|----------|---|
| L        | 1247 mm  | Length  |
| B        | 309 mm   | Width   |
| H        | 89 mm    | Height  |
| T        | 82 mm    | Depth   |
| DA(L)    | 1185 mm  | Cutting dimension length                                      |
| DA(B)    | 285 mm   | Cutting dimension width                                       |
| DS min   | 15 mm    | Ceiling thickness minimum                                     |
| DS max   | 40 mm    | Ceiling thickness maximum                                     |
| Et(min)  | 150 mm   | Ceiling distance minimum - minimum dimension (visible T-rail) |
| Et(AD)   | 150 mm   | Ceiling distance minimum (cut-out ceiling)                    |
| Et(TS)   | 250 mm   | Ceiling distance minimum - recommended (visible T-rail)       |
| Et(VS)   | 150 mm   | Ceiling distance minimum (concealed symmetrical)              |
| MLTS1    | 1250 mm  | Module dimension length (visible T-rail)                      |
| MLTS_1/2 | 1250     | Module dimension length (visible T-rail) 1/2                  |
| MLVS     | 1250 mm  | Module dimension length (concealed symmetrical)               |
| MBTS1    | 312.5 mm | Module dimension width (visible T-rail)                       |
| MBTS_1/2 | 312.5    | Module dimension width (visible T-rail) 1/2                   |
| MBVS     | 312.5 mm | Module dimension width (concealed symmetrical)                |