

Recessed downlight - Single lens/TriZone - direct wide distribution - IP 54

Housing made of sheet steel with cover ring made of die-cast aluminium painted in RAL 9016 traffic white. With mounting springs for installation without tools, suitable for ceiling thickness of 10mm-25mm. Housing colour traffic white RAL 9016; Direct wide beam light distribution via an individual lens/TriZone 85° designed with LEDiL's YASMEEN lens and a translucent glass pane. Including adjustable ETM driver wired ready for operation. Electrical connection via 0.5m long connection cable, 2x0.5mm². With the Changy-SR accessory refurbishment ring, a ceiling cut-out of 230-300mm is possible.

CHARACTERISTICS

Order number	36511074110
EAN number	4020863477494
Commodity code	94051190
Certification mark	IP 54/20, Protection class II, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING


Controller	Electronic multi-lumen driver, 4-steps (1 pcs.)
System output	19W-10W
Mains voltage	230V/50Hz
Energy efficiency class/light source	D

LIGHTING TECHNOLOGY


Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux/switching steps (EDM)	2300lm/19W, 2100lm/17W, 1700lm/14W, 1300lm/10W
LED service life	100000h L80/B10 (Tq 25°C/do not cover with insulation wool), 50000h L90/B50 (Tq 25°C/do not cover with insulation wool)
Luminaire luminous efficiency	130lm/W-120lm/W
Beam angle	85°
UGR lat./long.	22.9 / 22.9 (19W)

DEEP-LINK

<https://www.regiolux.de/en/article/36511074110>



Reference	LED 2300lm/19W 840
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	22.9 / 22.9



MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	246mm x 117mm
Depth	110.5mm
Ceiling system	cut-out ceilings [AD], Panel ceiling [PD] (module 100/200)
Ceiling cut-out (LxW/D)	229mm
Installation depth	165mm [AD]
Weight (net)	1.38kg
Type of installation	Ceiling installation individual mounting

Dimensions

H	117 mm	Height
D	246 mm	Diameter
T	110.5 mm	Depth
DA	229 mm	Cutting dimension diameter
DS min	10 mm	Ceiling thickness minimum
DS max	25 mm	Ceiling thickness maximum
Et(AD)	165 mm	Ceiling distance minimum (cut-out ceiling)
KL	144 mm	Length luminaire head or box for ballasts
KB	43 mm	Width luminaire head or box for ballasts
KH	30 mm	Height luminaire head or box for ballasts