

Surface-mounted downlight - Opal diffuser - direct wide distribution

Surface-mounted housing of die-cast aluminium painted in RAL 9016 traffic white, with driver wired ready for operation. Quick fit mounting plate with Snapfix quick release fastener and safety cable; Housing colour white; Direct, wide-beam light distribution using diffuse distribution opal diffuser. Integrated LED driver with luminaire wired ready for operation. Electrical connection via 3 individual terminals with plug-in contacts. Suitable for feed-through wiring. Further colours available on request.

CHARACTERISTICS

Order number	37691114140
EAN number	4020863472796
Commodity code	94051190
Certification mark	IP 20, Protection class I, F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Warranty period	5 years

DEEP-LINK

<https://www.regiolum.de/en/article/37691114140>

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	14W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	38 pieces/B10, 60 pieces/B16, 57 pieces/C10, 91 pieces/C16
Energy efficiency class/light source	D

LIGHTING TECHNOLOGY


Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RGO
Nominal luminous flux	1007lm
LED service life	50000h L85/B10 (Tq 25°C), 75000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	73lm/W
Beam angle	110°
UGR lat./long.	27.9 / 27.9

MECHANICS

Housing colour	white
Dimensions (LxWxH/DxH)	140mm x 115mm
Weight (net)	1.03kg
Type of installation	Ceiling-mounted single installation

Dimensions

H	115 mm	Height
D	140 mm	Diameter



Reference	LED 1000lm 830
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	27.9 / 27.9

