

Recessed spotlight - MIRO® High gloss faceted reflector - direct, narrow distribution

Housing made of die-cast aluminium, powder-coated, round design, die-cast aluminium heat sink for effective passive cooling, reflector unit gimbal-mounted, with fixing springs for installation without tools, suitable for ceiling thicknesses of 10 mm – 20 mm. Housing colour traffic white RAL 9016; Direct narrow-beam light distribution using high-gloss faceted reflector made of highly efficient MIRO aluminium with reflection coefficient of 99.8 %; clear safety glass; External driver with luminaire wired ready for operation. Electrical connection via 0.7m long connection cable, 2x0.75mm²+2x0.75mm². Luminaire including LED and driver. Interchangeable reflector 40°-100/110/144 available as an accessory. Adapter rings are available on request for installation in individual ceiling openings.

CHARACTERISTICS

Order number	37570036630
EAN number	4020863343539
Commodity code	94051190
Certification mark	IP 20, Protection class II, VDU 65°<3000, F, Indoor, CE
Special properties	Ready for IoT

ELECTRICAL ENGINEERING

Controller	Electronic driver DALI2 (1 pcs.)
System output	23W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	33 pieces/B10, 55 pieces/B16, 57 pieces/C10, 92 pieces/C16
Energy efficiency class/light source	D

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Nominal luminous flux	2504lm
LED service life	50000h L80/B50
Luminaire luminous efficiency	109lm/W
Beam angle	30°
UGR lat./long.	16.5 / 16.5 (30° reflector)

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	138mm x 94mm
Ceiling system	cut-out ceilings [AD]
Ceiling cut-out (LxW/D)	120mm
Installation depth	140mm [AD]
Weight (net)	0.4kg
Swivel and turn area (x/y/z)	± 30° / 0° / 360°
Type of installation	Ceiling installation individual mounting

Dimensions

H	94 mm	Height
D	138 mm	Diameter
DA	120 mm	Cutting dimension diameter
DS min	10 mm	Ceiling thickness minimum
DS max	20 mm	Ceiling thickness maximum
Et(AD)	140 mm	Ceiling distance minimum (cut-out ceiling)
KL	115 mm	Length luminaire head or box for ballasts
KB	53 mm	Width luminaire head or box for ballasts
KH	23 mm	Height luminaire head or box for ballasts

DEEP-LINK

<https://www.regiolux.de/en/article/37570036630>



Reference	LED 2500lm 830
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	16.5 / 16.5 (30° reflector)
VDU	65° < 3000cd/m ²

