

Furniture / mirror luminaire - Opal diffuser - direct/indirect distribution

Housing made of anodised extruded aluminium profile, screw-type end faces made of plastic coated white aluminium, vertical or horizontal wall installation possible, with integrated cable channel and protection rated cable entry. Housing colour natural anodised aluminum; Direct/indirect light distribution using opal diffuser made of ISCC-certified "TRUCIRCLE™" polycarbonate with a smooth surface Electrical connection via 3-pole connection terminal with plug-in contacts..

## CHARACTERISTICS

Order number	16161634125
EAN number	4020863321872
Commodity code	94051190
Certification mark	IP 44, Protection class I, ENEC10 VDE, Heat filament test 850°C, F, MM, Indoor, CE
Impact resistance (IK rating)	IK02 (10°C bis 35°C)
Ambient temperatur	ta 10°C to 35°C
Warranty period	5 years

## ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	9W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	100 pieces/B10, 160 pieces/B16, 120 pieces/C10, 200 pieces/C16
Energy efficiency class/light source	C

## LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	1041lm
LED service life	50000h L80/B10 (Tq 35°C)
Luminaire luminous efficiency	116lm/W


## MECHANICS

Housing colour	natural anodised aluminum
Dimensions (LxWxH/DxH)	600mm x 47mm x 82mm
Weight (net)	0.9kg
Cable entry KE (X/Y)	150mm/0mm
Type of installation	Wall mounting, Furniture mounting

## Dimensions

L	600 mm	Length
B	47 mm	Width
H	82 mm	Height
A1	350 mm	Mounting distance single mounting
X	150 mm	Distance cable infeed to the center of the luminaire on the X-axis
Y	0 mm	Distance cable infeed to the center of the luminaire on the Y-axis

## DEEP-LINK

<https://www.regiolum.de/en/article/16161634125>


Reference	LED 1000lm 830
ηLB	100 %
Φ ↓/↑	77 % / 23 %

