

High-bay luminaire - LED lens optics - direct narrow/wide distribution - IP 65

Housing made of die-cast aluminium, black powder-coated, rear of housing with integrated ring screw for suspension. Housing colour black; Direct narrow/wide-beam light distribution using LED lens optic; with clear cover made of safety glass. Integrated and exchangeable driver. Electric connection via 0.3m long connection cable, 3x1.0mm<sup>2</sup> and 2x0.5mm<sup>2</sup>. Refractor and refractor pane available as accessories. Suspension set CKH-AS and node chain KK for chain suspension, to be ordered separately.

**CHARACTERISTICS**

Order number	37372026194
EAN number	4020863468133
Commodity code	94051190
Certification mark	IP 65, Protection class I, F, D, Indoor, CE
Impact resistance (IK rating)	IK08 (-30°C bis 50°C)
Ambient temperatur	ta -30°C to 50°C
Special properties	Ready for IoT
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

**ELECTRICAL ENGINEERING**

Controller	Electronic driver DALI (1 pcs.)
Wiring	5x1mm <sup>2</sup>
System output	149W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	3 pieces/B10, 5 pieces/B16, 6 pieces/C10, 9 pieces/C16
Energy efficiency class/light source	C

**LIGHTING TECHNOLOGY**

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	5SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	23761lm
LED service life	50000h L80/B10 (Tq 50°C)
Luminaire luminous efficiency	159lm/W
Beam angle	85°
UGR lat./long.	26.2 / 26.2

**MECHANICS**


Housing colour	black
Dimensions (LxWxH/DxH)	370mm x 210mm
Weight (net)	5.41kg
Type of installation	Pendant individual mounting, Ceiling-mounted single installation

**Dimensions**

H	210 mm	Height
D	370 mm	Diameter

**DEEP-LINK**

<https://www.regiolux.de/en/article/37372026194>



Reference	LED 23800lm 840
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	26.2 / 26.2

