

Control system+sensor

Light/presence/HCL sensor for ceiling surface mounting. Presence detector for ceiling surface mounting with integrated DALI controller for HCL, activation of up to 50 DALI-DT8 luminaires in max. 3 function groups, integrated real-time clock; pre-set and freely adjustable HCL progression curves, manual operation via 3 conventional pushbuttons possible, extensions via accessories possible, integrated switching relay, parameter setting via BLE-IR adapter and smart phone or tablet (Android, iOS), detection range circular 360°, range: max. Ø 24 m laterally, max. Ø 8 m frontal, max. Ø 6.4 seated, mounting height min./max./recommended: 2 m / 10 m / 2.5 m

CHARACTERISTICS

Order number	84506031100
EAN number	4020863450022
Commodity code	90328900
Certification mark	IP 20, Protection class II, CE

ELECTRICAL ENGINEERING

Mains voltage	220-240V/50Hz
Control signal	DALI broadcast, DALI DT8

MECHANICS

Housing colour	white
Dimensions (LxWxH/DxH)	124mm x 85mm
Weight (net)	0.14kg
Type of installation	Ceiling-mounted single installation

Dimensions

H	85 mm	Height
D	124 mm	Diameter

DEEP-LINK

<https://www.regiolux.de/en/article/84506031100>

