

Sensor

Light/presence sensor for ceiling/luminaire installation. Light and presence sensor with adjustable presence detection range for luminaire and/or ceiling installation for connection to the DALIeco Control control unit; light and presence sensor via remote control can be activated/deactivated individually; function display with two-colour LED; motion detection range is adjustable; mounting height: 2...5m working range of light sensor: 20...800lx (measured at sensor); integrated Infrared remote control receiver; connection via 4p4c socket (RJ10) with reverse polarity protection;

CHARACTERISTICS

Order number	84501040100
EAN number	4020863291526
Commodity code	85176200
Certification mark	IP 20, CE

MECHANICS

Housing colour	grey
Dimensions (LxWxH/DxH)	48mm x 15mm x 17mm
Weight (net)	0.01kg
Type of installation	Housing flush mounting

Dimensions

L	48 mm	Length
B	15 mm	Width
H	17 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/84501040100>



LC SYSTEM

CHARACTERISTICS

Regiolux Classification	netlife easy
Control signal	DALI broadcast
Number of control gear (max)	32
Communication	Wired
Sensor technology	PIR - passive infrared
Installation height (min/max)	2m to 5m
Remote control	84501041200
Optional remote control	84501042100
Application	Office, Secondary rooms, Meeting rooms, Classrooms, Corridors
Function	Motion detection, presence detection, Daylight control, Manual dimming, Corridor function



MONITORING AREA

Mounting Height	2,5m	3,5m	5m
Ø max. sitting[S]	3,3m	5m	-
Ø max. radial[R]	5,3m	7m	7m
Ø max. tangential[T]	-	-	-

