

## Accessories - Wire suspension

Rectangular canopy L=317mm, metal ceiling cylinder, 2 wires D=1.2mm L=1900mm, 2 cross-spans L=190mm, white connection cable Housing colour traffic white RAL 9016/white; Light Control: netlife easy01C; Regiolux Classification: netlife easy; Control signal: DALI; Number of control gear (max): 32; Communication: Bluetooth; App name: Osram BT Config; Osram BT Control; Note: up to 4 DALI sensors or DALI push button coupler can also be connected; System extension: easy01S; Application: Office, Meeting rooms, Corridors, Classrooms, Secondary rooms; Function: Motion detection\*, Corridor function\*, presence detection\*, Daylight control\*, Tunable white (only with DT8 luminaires), Manual dimming, \*only by auxiliary devices. Suspension set with integrated receiver, rectangular canopy, individual steel cable suspension with connection cable 5x0.75mm<sup>2</sup>, suitable for suspended luminaires with DALI controllers, for stail SHL. LED light run Operation and configuration via the Osram BT Control app.

## CHARACTERISTICS

Order number	91210125121
EAN number	4020863377800
Commodity code	94059900
Certification mark	Indoor, CE

## DEEP-LINK

<https://www.regiolux.de/en/article/91210125121>

## ELECTRICAL ENGINEERING


Wiring	5x0.75mm <sup>2</sup>
--------	-----------------------

## MECHANICS

Housing colour	traffic white RAL 9016/white
Dimensions (LxWxDxH)	317mm x 44.5mm x 39mm
Weight (net)	0.6kg
Type of installation	Pendant individual mounting, Pendant light strip mounting

## Dimensions

L	317 mm	Length
B	44.5 mm	Width
H	39 mm	Height



## LC SYSTEM

### CHARACTERISTICS

<b>Regiolux Classification</b>	netlife easy
<b>Control signal</b>	DALI
<b>Number of control gear (max)</b>	32
<b>Communication</b>	Bluetooth
<b>App name</b>	Osram BT Config; Osram BT Control
<b>Note</b>	up to 4 DALI sensors or DALI push button coupler can also be connected
<b>System extension</b>	easy01S
<b>Application</b>	Office, Meeting rooms, Corridors, Classrooms, Secondary rooms
<b>Function</b>	Motion detection*, Corridor function*, presence detection*, Daylight control*, Tunable white (only with DT8 luminaires), Manual dimming, *only by auxiliary devices

