

Accessories - Pattern wire suspension with ceiling cylinder

Rectangular canopy L=317mm vw, metal ceiling cylinder, 2 wires D=1.2 L=1900; Housing colour traffic white RAL 9016; Anschlussleitung 5x0,75. Light Control: netlife flex10L; Regiolux Classification: netlife flex; Control signal: DALI, Radio; Number of control gear (max): 5; Communication: Bluetooth; App name: Casambi, 4remote BT; System compatibility: flex10; flex10X; flex10L; flex37; flex39; Note: compatible with Casambi; Application: Office, Meeting rooms, Secondary rooms, Retail, Corridors, Garages, Classrooms, Sports facilities; Function: Motion detection\*, Corridor function\*, Guided Light\*, HCL (only with DT8 luminaires), presence detection\*, Daylight control, Tunable white (only with DT8 luminaires), Manual dimming, \*only by auxiliary devices. Suspension set with integrated receiver Operation and configuration via the Casambi app.

## CHARACTERISTICS

Order number	91101025121
EAN number	4020863377725
Commodity code	94059900
Certification mark	Indoor, CE

## ELECTRICAL ENGINEERING

Wiring	5x0.75mm <sup>2</sup>
--------	-----------------------

## MECHANICS



Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	317mm x 44.5mm x 39mm
Weight (net)	0.58kg
Type of installation	Pendant individual mounting, Pendant light strip mounting

## Dimensions

L	317 mm	Length
B	44.5 mm	Width
H	39 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/91101025121>



## LC SYSTEM

### CHARACTERISTICS

<b>Regiolux Classification</b>	netlife flex
<b>Control signal</b>	DALI, Radio
<b>Number of control gear (max)</b>	5
<b>Communication</b>	Bluetooth
<b>App name</b>	Casambi, 4remote BT
<b>System compatibility</b>	flex10; flex10X; flex10L; flex37; flex39
<b>Note</b>	compatible with Casambi
<b>Application</b>	Office, Meeting rooms, Secondary rooms, Retail, Corridors, Garages, Classrooms, Sports facilities
<b>Function</b>	Motion detection*, Corridor function*, Guided Light*, HCL (only with DT8 luminaires), presence detection*, Daylight control, Tunable white (only with DT8 luminaires), Manual dimming, *only by auxiliary devices

