

Luminaire with a higher protection rating - Opal diffuser - direct distribution

Housing made of glass-fibre reinforced polyester, with PUR foam age-resistant sealing in the surrounding edge, stainless steel diffuser clips, device mount made of sheet steel painted white. Housing with increased chemical resistance. Housing colour light grey; Deep-drawn acrylic glass diffuser with opal, smooth surface; Integrated driver. Electrical connection via 3-pole connection terminal with plug-in contacts.. Swivel mounting bracket SBB to be ordered separately.

CHARACTERISTICS

Order number	56612024110
EAN number	4020863334940
Commodity code	94051140
Certification mark	IP 65, Protection class I, F, D, HACCP DIN10500/Food/IFS/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (0°C), IK04 (25°C)
Ambient temperatur	ta 0°C to 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	31W
Mains voltage	230V/50Hz
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG0
Nominal luminous flux	4611lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	149lm/W
UGR lat./long.	24.5 / 21.8

MECHANICS


Housing colour	light grey
Dimensions (LxWxH/DxH)	1300mm x 105mm x 117mm
Weight (net)	1.9kg
Cable entry KE (X/Y)	650mm/0mm
Type of installation	Ceiling-mounted single installation, Pendant individual mounting, Wall mounting, Mounting rail installation

Dimensions

L	1300 mm	Length
B	105 mm	Width
H	117 mm	Height
A1	800 mm	Mounting distance single mounting
A3	505 mm	Mounting distance between luminaires in a light run arrangement
X	650 mm	Distance cable infeed to the center of the luminaire on the X-axis
Y	0 mm	Distance cable infeed to the center of the luminaire on the Y-axis

DEEP-LINK

<https://www.regiolux.de/en/article/56612024110>



Reference	LED 4500lm 840
ηLB	100 %
Φ ↓/↑	91 % / 9 %
UGR lat./long.	24.5 / 21.8

