

Pendant luminaire - Satin-finished diffuser - direct/indirect distribution

Sheet steel housing with square design; prepared for fixing end faces or luminaire connectors made of steel; Housing colour silver grey/white aluminium RAL 9006; Direct/indirect light distribution; glare suppression using diffuse distribution frosted polycarbonate profile; diffuser is optically seamless for light run mounting; Electrical connection and connection of control cable using 5-pole connection terminal with plug-in contacts. Required accessories: order face ends, connectors, through-wiring and Y-wire suspensions SAY-KS/SAYE-KL and a height-adjustable suspension set with a canopy and an integrated light control with a 1900 mm suspension length separately according to luminaire arrangements.

CHARACTERISTICS

Order number	60511026685
EAN number	4020863319091
Commodity code	94051190
Certification mark	IP 20, Protection class I, F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Special properties	Ready for IoT
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver DALI2 (1 pcs.)
System output	23W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	18 pieces/B10, 30 pieces/B16, 31 pieces/C10, 50 pieces/C16
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	2846lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	123lm/W
UGR lat./long.	20.3 / 20.4

MECHANICS

Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxH/DxH)	1176mm x 85mm x 72mm
Weight (net)	3.2kg
Type of installation	Pendant individual mounting, Pendant light strip mounting

Dimensions

L	1176 mm	Length
B	85 mm	Width
H	72 mm	Height
A1	1100 mm	Mounting distance single mounting
A2	1138 mm	Mounting distance 1st luminaire of the light run
A3	1176 mm	Mounting distance between luminaires in a light run arrangement
P min	150 mm	Minimum suspension length
P max	1900 mm	Maximum suspension length

DEEP-LINK

<https://www.regiolux.de/en/article/60511026685>



