

Pendant luminaire - Satin-finished diffuser - direct/indirect distribution

Sheet steel housing with square design; prepared for fixing end faces or luminaire connectors made of steel; Housing colour traffic white RAL 9016; Direct/indirect light distribution; glare suppression using diffuse distribution frosted polycarbonate profile; diffuser is optically seamless for light run mounting; Electrical connection via 3-pole connection terminal with plug-in contacts. Required accessories: order end faces, connectors, through-wiring and Y-wire-rope suspensions SAYE-PS/SAY-DZ with 1900 mm suspension length separately according to luminaire arrangements.

CHARACTERISTICS

Order number	60511024180
EAN number	4020863318421
Commodity code	94051190
Certification mark	IP 20, Protection class I, F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	23W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	21 pieces/B10, 34 pieces/B16, 35 pieces/C10, 57 pieces/C16
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	2846lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	123lm/W
UGR lat./long.	20.3 / 20.4

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1176mm x 85mm x 72mm
Weight (net)	3.2kg
Type of installation	Pendant individual mounting, Pendant light strip mounting

Dimensions

L	1176 mm	Length
B	85 mm	Width
H	72 mm	Height
A1	1100 mm	Mounting distance single mounting
A2	1138 mm	Mounting distance 1st luminaire of the light run
A3	1176 mm	Mounting distance between luminaires in a light run arrangement
P min	150 mm	Minimum suspension length
P max	1900 mm	Maximum suspension length

DEEP-LINK

<https://www.regiolux.de/en/article/60511024180>



Reference	LED 2700lm 840
ηLB	100 %
Φ ↓/↑	60 % / 40 %
UGR lat./long.	20.3 / 20.4

