

Suspended luminaire/light run feed luminaire - Micro-prismatic diffuser - direct/indirect distribution

Ultra-flat luminaire housing design, painted extruded aluminium profile, visible installation height 10/24mm; Housing colour black RAL 9005; Direct/indirect light distribution, direct share by means of a microprism made of PMMA, homogeneous light emission through lateral LED light coupling in Light Guide panel and semi-diffuse, reflective white coating, with special decoupling technology for defined ceiling illumination; for VDU workstations, omnidirectional glare reduction according to the current norm DIN-EN 12464-1. Integrated LED driver design. Electrical connection via integrated transparent connection cable 3x0.75mm², length 1900mm, stripped cable ends. Komplettes höhenverstellbares Pendel-Set im Lieferumfang enthalten.

CHARACTERISTICS

Order number	46202024174
EAN number	4020863380596
Commodity code	94051190
Certification mark	IP 20, Protection class I, VDU 65° < 3000, F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	36W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	15 pieces/B10, 25 pieces/B16, 26 pieces/C10, 42 pieces/C16
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	4568lm
LED service life	50000h L90/B10 (Tq 25°C)
Luminaire luminous efficiency	128lm/W
UGR lat./long.	16.3 / 15.8

MECHANICS


Housing colour	black RAL 9005
Dimensions (LxWxH/DxH)	1250mm x 321mm x 24mm
Weight (net)	4.9kg
Type of installation	Pendant individual mounting, Pendant light strip mounting

Dimensions

L	1250 mm	Length
B	321 mm	Width
H	24 mm	Height
A1	700 mm	Mounting distance single mounting
P min	150 mm	Minimum suspension length
P max	1900 mm	Maximum suspension length

DEEP-LINK

<https://www.regiolum.de/en/article/46202024174>



Reference	LED 4600lm 830
ηLB	100 %
Φ ↓/↑	74 % / 26 %
UGR lat./long.	16.3 / 15.8
VDU	65° < 3000cd/m ²

