

Pendant luminaire - Frosted diffuser - direct/indirect distribution - homogeneous light output through LED edge light injection

Ultra-flat luminaire housing, extruded aluminium profile, naturally anodised, visible installation height 30 mm; end faces and side parts made of naturally anodised aluminium with continuous longitudinal groove, rounded towards the bottom of the luminaire. Housing colour natural anodised aluminum; Light distribution direct/indirect distribution, direct component using frosted PMMA pane, homogeneous light emission through lateral LED light coupling and aluminium reflector fitted on top of it in a highly reflective white coating, with micro perforation for the indirect light component. Two integrated DALI LED drivers device type 8 (DT8). Electrical connection via integrated transparent connection cable 5x0.75mm², length 1900mm, stripped cable ends. Y-wire suspensions and a ceiling canopy of extruded aluminium profile, with silver grey coated plastic end faces are included in scope of delivery. DALI control units must be ordered separately. Luminaire with Tunable White continuously adjustable colour temperatures, for implementing human-centric daylight simulations (HCL).

CHARACTERISTICS

Order number	43254026915
EAN number	4020863329564
Commodity code	94051190
Certification mark	IP 20, Protection class I, F, HCL, Indoor, CE
Impact resistance (IK rating)	IK03
Ambient temperatur	ta 25°C
Special properties	Ready for IoT
Warranty period	5 years

ELECTRICAL ENGINEERING

Controller	Electronic driver DALI device type 8 (1 pcs.)
System output	55W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	7 pieces/B10, 11 pieces/B16, 11 pieces/C10, 18 pieces/C16
Energy efficiency class/light source	E

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 90 / 2700K-6500K continuously adjustable
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	4720lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	86lm/W
UGR lat./long.	19.2 / 19.1

MECHANICS


Housing colour	natural anodised aluminum
Dimensions (LxWxH/DxH)	1480mm x 330mm x 30mm
Weight (net)	9.1kg
Type of installation	Pendant individual mounting

Dimensions

L	1480 mm	Length
B	330 mm	Width
H	30 mm	Height
A1	863 mm	Mounting distance single mounting
P min	150 mm	Minimum suspension length
P max	1900 mm	Maximum suspension length

DEEP-LINK

<https://www.regiolux.de/en/article/43254026915>



Reference	LED 4700lm 927-965
ηLB	100 %
Φ ↓/↑	84 % / 16 %
UGR lat./long.	19.2 / 19.1

