

Pendant luminaire - Micro-prismatic diffuser - direct/indirect distribution - homogeneous light output through LED edge light injection

Ultra-flat luminaire housing, extruded aluminium profile, naturally anodised, visible installation height 30 mm; end faces and side parts made of naturally anodised aluminium with continuous longitudinal groove, rounded towards the bottom of the luminaire. Housing colour natural anodised aluminium; Direct/indirect light distribution, direct component using microprism made of PMMA, homogeneous light emission through lateral LED light coupling and overlying aluminium reflector with highly reflective white coating, with micro-perforation for the indirect light component; for workstations, omnidirectional glare reduction according to the current DIN-EN 12464-1 standard.

Integrated LED driver design. Electrical connection via integrated transparent connection cable 5x0.75mm², length 1900mm, stripped cable ends. Y-wire suspensions and a ceiling canopy of extruded aluminium profile, with silver grey coated plastic end faces are included in scope of delivery. Complete height-adjustable suspension set with canopy and integrated light control available separately as accessories.

CHARACTERISTICS

| | |
|-------------------------------|--|
| Order number | 43251026675 |
| EAN number | 4020863304509 |
| Commodity code | 94051190 |
| Certification mark | IP 20, Protection class I, VDU 65°<3000, F, Indoor, CE |
| Impact resistance (IK rating) | IK03 |
| Ambient temperatur | ta 25°C |
| Special properties | Ready for IoT |
| Warranty period | 5 years |

ELECTRICAL ENGINEERING

| | |
|--------------------------------------|--|
| Controller | Electronic driver DALI2 (1 pcs.) |
| System output | 55W |
| Mains voltage | 230V/50Hz |
| Circuit breakers (inrush current) | 13 pieces/B10, 24 pieces/B16, 25 pieces/C10, 40 pieces/C16 |
| Energy efficiency class/light source | C |

LIGHTING TECHNOLOGY

| | |
|-------------------------------|---|
| Placement | LED, Colour rendering/Light colour CRI ≥ 80 / 4000K |
| Colour tolerance (MacAdam) | 3SDCM |
| Nominal luminous flux | 6295lm |
| LED service life | 50000h L80/B10 (Tq 25°C) |
| Luminaire luminous efficiency | 115lm/W |
| UGR lat./long. | 18.2 / 18.3 |

MECHANICS


| | |
|------------------------|-----------------------------|
| Housing colour | natural anodised aluminum |
| Dimensions (LxWxH/DxH) | 1480mm x 330mm x 30mm |
| Weight (net) | 7.9kg |
| Type of installation | Pendant individual mounting |

Dimensions

| | | |
|-------|---------|-----------------------------------|
| L | 1480 mm | Length |
| B | 330 mm | Width |
| H | 30 mm | Height |
| A1 | 863 mm | Mounting distance single mounting |
| P min | 150 mm | Minimum suspension length |
| P max | 1900 mm | Maximum suspension length |

DEEP-LINK

<https://www.regiolum.de/en/article/43251026675>



| | |
|----------------|-----------------------------|
| Reference | LED 6300lm 840 |
| ηLB | 100 % |
| Φ ↓/↑ | 84 % / 16 % |
| UGR lat./long. | 18.2 / 18.3 |
| VDU | 65° < 3000cd/m ² |

