

Busbar function module device mount

Device mount with integrated universal 3-phase conductor rail (useable length 680 mm) made of galvanised, profiled sheet steel for the combination of accent lighting and general lighting; surface coated with polyester resin enamel; with three rotary catches for rapid mounting to mounting rail. Housing colour traffic white RAL 9016; Heat-resistant cables including fixed, 7-pin, quick-fit plug connector with toolless phase preselection and locating finger. Suitable for luminaires with 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	18478150100
EAN number	4020863357512
Commodity code	94059900
Certification mark	IP 20, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Mains voltage	230V/NaHz
---------------	-----------

MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1532mm x 55mm x 45mm
Weight (net)	2.3kg
Type of installation	Mounting rail system installation

Dimensions

L	1532 mm	Length
B	55 mm	Width
H	45 mm	Height

DEEP-LINK

https://www.regiolux.de/en/article/18478150100

