

## Busbar function module device mount

Device mount with integrated universal 3-phase conductor rail (useable length 680 mm) made of galvanised, profiled sheet steel for the combination of accent lighting and general lighting; surface coated with polyester resin enamel; with three rotary catches for rapid mounting to mounting rail. Housing colour traffic white RAL 9016; Heat-resistant cables including fixed, 7-pin, quick-fit plug connector with toolless phase preselection and locating finger. Suitable for luminaires with 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

|                    |                                       |
|--------------------|---------------------------------------|
| Order number       | 18478150100                           |
| EAN number         | 4020863357512                         |
| Commodity code     | 94059900                              |
| Certification mark | IP 20, Protection class I, Indoor, CE |

## ELECTRICAL ENGINEERING

|               |           |
|---------------|-----------|
| Mains voltage | 230V/NaHz |
|---------------|-----------|

## MECHANICS

|                        |                                   |
|------------------------|-----------------------------------|
| Housing colour         | traffic white RAL 9016            |
| Dimensions (LxWxH/DxH) | 1532mm x 55mm x 45mm              |
| Weight (net)           | 2.3kg                             |
| Type of installation   | Mounting rail system installation |

## Dimensions

|   |         |        |
|---|---------|--------|
| L | 1532 mm | Length |
| B | 55 mm   | Width  |
| H | 45 mm   | Height |

## DEEP-LINK

<https://www.regiolux.de/en/article/18478150100>

