

netlife light management function module device mount

Blank cover made of galvanised, profiled sheet steel; surface with polyester resin enamel coating; with two rotary catches for rapid fitting in the mounting rail, for the integration of sensors and control unit in the light run; Housing colour traffic white RAL 9016; Light Control: netlife easy19; Regiolux Classification: netlife easy; Control signal: Slave signal; Communication: Wired; Sensor technology: PIR - passive infrared; Installation height (min/max): 2m to 10m; Monitoring area: max. D=48m; System compatibility: easy06; easy15; System extension: easy19; Application: Industry, Logistics centres, Garages, Corridors; Function: Motion detection, presence detection. Wired ready for connection via integrated connector. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	84186580202
EAN number	4020863274192
Commodity code	90328900
Certification mark	IP 20, Indoor, CE
Special properties	Advanced Services

ELECTRICAL ENGINEERING

Controller	easy19
Mains voltage	230V/50Hz

MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1532mm x 102mm x 99mm
Weight (net)	1.1kg
Type of installation	Mounting rail system installation

Dimensions

L	1532 mm	Length
B	102 mm	Width
H	99 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/84186580202>



