

Variable device mount - Linear.Lens.Profile - direct, narrow distribution - visually continuous

Device mount made of galvanised, profiled sheet steel; surface coated with polyester resin. Housing colour traffic white RAL 9016; Direct narrow light distribution using Linear.Lens.Profile made of clear PMMA plastic.

Optically seamless light run. Heat-resistant cables including connection cable 1 m and rapid installation plug connector with tool-less phase pre-selection and locating finger. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

Order number	18324606650
EAN number	4020863336296
Commodity code	94051190
Certification mark	IP 20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (10°C bis 35°C)
Ambient temperatur	ta 10°C to 35°C
Special properties	Ready for IoT
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

## ELECTRICAL ENGINEERING

Controller	Electronic driver DALI2 (1 pcs.)
System output	64W
Mains voltage	230V/50Hz
Energy efficiency class/light source	B

## LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	10955lm
LED service life	50000h L80/B10 (Tq 35°C)
Luminaire luminous efficiency	171lm/W
Beam angle	60° (C0) / 120° (C90)
UGR lat./long.	21.1 / 30.0

## MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1531mm x 63mm x 41mm
Weight (net)	2.1kg
Type of installation	Mounting rail system installation

## Dimensions

L	1531 mm	Length
B	63 mm	Width
H	41 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/18324606650>



Reference	LED 11000lm 840
ηLB	100 %
Φ ↓/↑	99 % / 1 %
UGR lat./long.	21.1 / 30.0

