

Variable device mount - Linear.Lens.Profile - direct, narrow distribution - visually continuous

Device mount made of galvanised, profiled sheet steel; surface coated with polyester resin.

Fastening without tools with two integrated lateral lever locks. LED unit in housing length for optically seamless light run. Variably positionable on the mounting rail. Housing colour traffic white RAL 9016; Direct narrow light distribution using Linear.Lens.Profil made of clear PMMA plastic.

Optically seamless light run. Heat-resistant cables including connection cable 1 m and rapid installation plug connector with tool-less phase pre-selection and locating finger. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	18324504150
EAN number	4020863336135
Commodity code	94051190
Certification mark	IP 20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (10°C bis 40°C)
Ambient temperatur	ta 10°C to 40°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	42W
Mains voltage	230V/50Hz
Energy efficiency class/light source	B

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	7539lm
LED service life	50000h L80/B10 (Tq 40°C)
Luminaire luminous efficiency	181lm/W
Beam angle	60° (C0) / 120° (C90)
UGR lat./long.	19.8 / 28.7

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1531mm x 55mm x 41mm
Weight (net)	1.9kg
Type of installation	Mounting rail system installation

Dimensions

L	1531 mm	Length
B	55 mm	Width
H	41 mm	Height

DEEP-LINK

<https://www.regiolum.de/en/article/18324504150>



Reference	LED 8000lm 840
ηLB	100 %
Φ ↓/↑	99 % / 1 %
UGR lat./long.	19.8 / 28.7

