

Device mount - Frosted diffuser - direct/indirect diffuse distribution - visually continuous

Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated lateral lever locks. LED unit in housing length for optically seamless light run. Housing colour traffic white RAL 9016; Direct light distribution, frosted diffuser made of PMMA plastic. Continuous row lighting design. Heat-resistant cables including fixed 3-pole rapid installation plug connector with tool-free phase preselection and locating finger The device mount is variably adjustable with multi-lumen. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	18199404100
EAN number	4020863480807
Commodity code	94051190
Certification mark	IP 20, Protection class I, ENEC10 VDE, F, Indoor, CE
Impact resistance (IK rating)	IK03 (25°C bis 35°C)
Ambient temperatur	ta 25°C to 35°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic multi-lumen driver, 4-steps (1 pcs.)
System output	61W-42W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	10 pieces/B10, 16 pieces/B16, 10 pieces/C10, 16 pieces/C16
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux/switching steps (EDM)	9200lm/61W, 8400lm/55W, 7500lm/49W, 6700lm/42W
LED service life	50000h L80/B10 (Tq 35°C)
Luminaire luminous efficiency	158lm/W-150lm/W
Beam angle	110° (C0) / 125° (C90)
UGR lat./long.	26.8 / 31.3 (61W)

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxDxH)	1531mm x 55mm x 42mm
Weight (net)	1.32kg
Type of installation	Mounting rail system installation

Dimensions

L	1531 mm	Length
B	55 mm	Width
H	42 mm	Height

DEEP-LINK

<https://www.regiolum.de/en/article/18199404100>



Reference	LED 9200lm/61W 840
η_{LB}	100 %
Φ ↓/↑	93 % / 7 %
UGR lat./long.	26.8 / 31.3

