

Mounting rail - Universal mounting rail, current taps every 1535 mm, for device mount module /1500

Torsion-resistant support rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal support rail suitable for light runs of all protection classes IP20 to IP64; Housing colour traffic white RAL 9016; Ribbon cabling installed and wired to quick-fit socket unit in the factory. Please order separately connection and assembly accessories as well as rail end pieces and connectors.

CHARACTERISTICS

| | |
|--------------------|--|
| Order number | 18262580100 |
| EAN number | 4020863035847 |
| Commodity code | 94059900 |
| Certification mark | IP 20/40/54/64, Protection class I, Indoor, CE |

ELECTRICAL ENGINEERING

| | |
|--------|----------------------|
| Wiring | 5x2.5mm ² |
|--------|----------------------|

MECHANICS

| | |
|------------------------|-----------------------------------|
| Housing colour | traffic white RAL 9016 |
| Dimensions (LxWxH/DxH) | 3070mm x 63mm x 46mm |
| Weight (net) | 3.3kg |
| Type of installation | Mounting rail system installation |

Dimensions

| | | |
|---|---------|--------|
| L | 3070 mm | Length |
| B | 63 mm | Width |
| H | 46 mm | Height |

DEEP-LINK

<https://www.regiolux.de/en/article/18262580100>

