

netlife light management function module device mount IP 54

Blank cover IP54 made of galvanised, profiled sheet steel with zinc coating and combined with polyester resin paint guarantees good corrosion protection; with two rotary catches for rapid fitting in the support rail; for bridging non-illuminated light run units, reflector mounting possible, sealed with all-round closed seal to the support rail to guarantee the protection type. Housing colour traffic white RAL 9016; Light Control: netlife easy15; Regiolux Classification: netlife easy; Control signal: DALI2-broadcast; Supported DALI parts: 201(DT0), 207(DT6), 208(DT7); DALI-output nom.: 80mA; Communication: Wired; Sensor technology: PIR - passive infrared; Installation height (min/max): 2m to 10m; Monitoring area: max. D=34m; Remote control: 84506028100; Optional remote control: 84506021200 +App; App name: B.E.G. One; System extension: easy19; Application: Office, Meeting rooms, Corridors, Industry, Classrooms, Secondary rooms, Logistics centres, Garages; Function: Daylight control, Manual dimming, Motion detection, Corridor function, presence detection. Wired ready for connection via integrated connector. Limited phase selection when pushbuttons and/or slave sensors are used. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	84181027205
EAN number	4020863321681
Commodity code	90328900
Certification mark	IP 54, Indoor, CE
Special properties	Ready for IoT

ELECTRICAL ENGINEERING

Controller	easy15
Mains voltage	230V/50Hz

MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1536mm x 110mm x 107mm
Weight (net)	1.2kg
Type of installation	Mounting rail system installation

Dimensions

L	1536 mm	Length
B	110 mm	Width
H	107 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/84181027205>



