

Variable Device mount functional module netlife light management

Device mount made of a galvanised, profiled steel sheet; surface with polyester resin enamel coating; with two rotary catches for rapid fitting in the mounting rail, for the integration of sensors and control unit in the light run; can be positioned variable on the mounting rail. Housing colour traffic white RAL 9016; Electrical connection by means of a 0.7m connection cable for variable device mount positioning in the light run with freely positionable phases. Light Control: netlife easy19; Regiolux Classification: netlife easy; Control signal: Slave signal; Communication: Wired; Sensor technology: PIR - passive infrared; Installation height (min/max): 2m to 10m; Monitoring area: max. D=48m; System compatibility: easy06; easy15; System extension: easy19; Application: Industry, Logistics centres, Garages, Corridors; Function: Motion detection, presence detection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. The easy 19 functional modules should be combined with the SRT support rail with feed-through wiring 5x2.5 / 6x1.5 mm². netlife easy system; straightforward in-house project engineering; easy installation; preset functions; simple commissioning via remote control, app, DIP switch, rotary knob, etc.

CHARACTERISTICS

Order number	19150700190
EAN number	4020863421374
Commodity code	90328900
Certification mark	IP 20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Special properties	Advanced Services

ELECTRICAL ENGINEERING

Controller	easy19
Mains voltage	230V/50Hz

MECHANICS



Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	765mm x 102mm x 99mm
Weight (net)	0.9kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	765 mm	Length
B	102 mm	Width
H	99 mm	Height

DEEP-LINK


<https://www.regiolux.de/en/article/19150700190>



LC SYSTEM

CHARACTERISTICS

Regiolux Classification	netlife easy
Control signal	Slave signal
Communication	Wired
Sensor technology	PIR - passive infrared
Installation height (min/max)	2m to 10m
System compatibility	easy06; easy15
System extension	easy19
Application	Industry, Logistics centres, Garages, Corridors
Function	Motion detection, presence detection



MONITORING AREA

Mounting Height	3,5m	10m
Ø max. sitting[S]	9m	-
Ø max. radial[R]	-	16m
Ø max. tangential[T]	-	48m

