

Variable Device mount functional module netlife light management

Device mount made of a galvanised, profiled steel sheet; surface with polyester resin enamel coating; with two rotary catches for rapid fitting in the mounting rail, for the integration of sensors and control unit in the light run; can be positioned variable on the mounting rail. Housing colour black RAL 9005; Electrical connection by means of a 0.7m connection cable for variable device mount positioning in the light run with freely positionable phases. Light Control: netlife easy48; Regiolux Classification: netlife easy; Control signal: Switch; Number of control gear (max): 400W LED; Communication: Wired; Sensor technology: PIR - passive infrared; Installation height (min/max): 4m to 14m; Monitoring area: max. D=20m; Remote control: 84501101203; Optional remote control: 84501101200 +App; App name: Steinel smart remote; Application: Industry, Logistics centres, Corridors, Garages; Function: Motion detection, Switch. When used with 7-pole rail, the contacts in the device mount must be reconnected. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

Order number	19150700484
EAN number	4020863466016
Commodity code	85365080
Certification mark	IP 20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Special properties	Advanced Services

## ELECTRICAL ENGINEERING

Controller	easy48
Mains voltage	230V/50Hz

## MECHANICS



Housing colour	black RAL 9005
Dimensions (LxWxH/DxH)	765mm x 95mm x 88mm
Weight (net)	0.9kg
Type of installation	Mounting rail system installation, Light structure

## Dimensions

L	765 mm	Length
B	95 mm	Width
H	88 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19150700484>



## LC SYSTEM

### CHARACTERISTICS

Regiolux Classification	netlife easy
Control signal	Switch
Number of control gear (max)	400W LED
Communication	Wired
Sensor technology	PIR - passive infrared
Installation height (min/max)	4m to 14m
Remote control	84501101203
Optional remote control	84501101200 +App
App name	Steinel smart remote
Application	Industry, Logistics centres, Corridors, Garages
Function	Motion detection, Switch



### MONITORING AREA

Mounting Height	5m	10m	14m
Ø max. sitting[S]	-	-	-
Ø max. radial[R]	11m	14,5m	-
Ø max. tangential[T]	34,5m	28m	20m

