

Variable LED device mount function module spotlight spotty - High gloss faceted reflector - direct, narrow distribution

Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin enamel; with rotary catches for rapid fitting in the mounting rail, spotlight unit made of die-cast aluminium, powder-coated housing, 350° rotation and 90° swivel angle. Device mount can be positioned variably on the mounting rail. Housing colour silver grey/white aluminium RAL 9006; Direct, narrow-beam light distribution using a faceted high-gloss reflector made of highly efficient MIRO-SILVER aluminium; clear safety glass. Electrical connection by means of a 0.7 m connection cable for variable device mount positioning in the light run with 3-pin, quick-fit plug connector with free phase positioning. Interchangeable reflector 20°/50 is available as an accessory. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

Order number	19105504015
EAN number	4020863388714
Commodity code	94051190
Certification mark	IP 20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (10°C bis 25°C)
Ambient temperatur	ta 10°C to 25°C
Warranty period	5 years

## ELECTRICAL ENGINEERING

Controller	Electronic driver (2 pcs.)
System output	69W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	11 pieces/B10, 17 pieces/B16, 18 pieces/C10, 29 pieces/C16
Energy efficiency class/light source	D

## LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	7968lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	115lm/W
UGR lat./long.	25.5 / 25.5

## MECHANICS


Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxDxH)	765mm x 55mm x 201mm
Weight (net)	2.5kg
Swivel and turn area (x/y/z)	+ 90° / 0° / 335°
Type of installation	Mounting rail system installation, Light structure

## Dimensions

L	765 mm	Length
B	55 mm	Width
H	201 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19105504015>



Reference	LED 8000lm 840
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	25.5 / 25.5

