

Device mount functional module universal 3-phase track

Device mount with integrated universal 3-phase conductor rail with DALI (useable length 660 mm) made of a galvanised, profiled steel sheet for the combination of accent lighting and general lighting; surface coated with polyester resin enamel; with rotary catches for rapid mounting to mounting rail. Housing colour black RAL 9005; Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. Suitable for luminaires with a 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac. The useful length of the 3-phase busbar with DALI enables the mounting of 3 spotty or 5 emphara spotlights. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

| | |
|--------------------|---------------------------------------|
| Order number | 19040000014 |
| EAN number | 4020863383344 |
| Commodity code | 94059900 |
| Certification mark | IP 20, Protection class I, Indoor, CE |

ELECTRICAL ENGINEERING

| | |
|---------------|------------|
| Mains voltage | 230V/NaNHZ |
|---------------|------------|

MECHANICS

| | |
|------------------------|--|
| Housing colour | black RAL 9005 |
| Dimensions (LxWxH/DxH) | 1532mm x 55mm x 44mm |
| Weight (net) | 2.4kg |
| Type of installation | Mounting rail system installation, Light structure |

Dimensions

| | | |
|---|---------|--------|
| L | 1532 mm | Length |
| B | 55 mm | Width |
| H | 44 mm | Height |

DEEP-LINK

| |
|---|
| https://www.regiolux.de/en/article/19040000014 |
|---|

