

Variable device mount functional module universal 3-phase track SRGVD

Device mount with integrated universal 3-phase track (useable length 280 mm) made of galvanised, profiled sheet steel for the combination of accent lighting and general lighting; surface coated with polyester resin enamel; with three rotary catches for rapid mounting to mounting rail. Can be variably positioned on the mounting rail. Housing colour black RAL 9005; Electrical connection by means of a 0.7m connection cable for variable positioning of the device mount with a 5-pin, quick-fit plug connector in the light run and free phase pre-selection. Suitable for luminaires with a 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac. The useful length of the 3-phase busbar with DALI enables the mounting of 1 spotty or 2 emphara spotlights. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

|                    |                                       |
|--------------------|---------------------------------------|
| Order number       | 19040000024                           |
| EAN number         | 4020863382620                         |
| Commodity code     | 94059900                              |
| Certification mark | IP 20, Protection class I, Indoor, CE |

## ELECTRICAL ENGINEERING

|               |           |
|---------------|-----------|
| Mains voltage | 230V/NaHz |
|---------------|-----------|

## MECHANICS

|                      |  |
|----------------------|--|
| Housing colour       | black RAL 9005                                     |
| Dimensions (LxWxDxH) | 765mm x 55mm x 45mm                                |
| Weight (net)         | 1.2kg  |
| Type of installation | Mounting rail system installation, Light structure |

## Dimensions

|   |        |        |
|---|--------|--------|
| L | 765 mm | Length |
| B | 55 mm  | Width  |
| H | 45 mm  | Height |

## DEEP-LINK

<https://www.regiolux.de/en/article/19040000024>

