

Variable device mount functional module universal 3-phase track SRGVD

Device mount with integrated universal 3-phase track (useable length 660 mm) made of galvanised, profiled sheet steel for the combination of accent lighting and general lighting; surface coated with polyester resin enamel; with three rotary catches for rapid mounting to mounting rail. Can be variably positioned on the mounting rail. Housing colour traffic white RAL 9016; Electrical connection by means of a 1m connection cable for variable device mount positioning with a 5-pin, quick-fit plug connector in the light run with free phase pre-selection. Suitable for luminaires with a 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac. The useful length of the 3-phase busbar with DALI enables the mounting of 3 spotty or 5 emphara spotlights. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19040000030
EAN number	4020863421350
Commodity code	94059900
Certification mark	IP 20, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Mains voltage	230V/NaHz
---------------	-----------

MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1532mm x 55mm x 45mm
Weight (net)	2.5kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	1532 mm	Length
B	55 mm	Width
H	45 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19040000030>

