

Device mount - Opal diffuser - direct/indirect distribution - visually continuous

Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with integrated side lever catches for rapid fitting in the mounting rail. LED unit in housing length for a continuous effect light run Housing colour traffic white RAL 9016; Direct/indirect light distribution, opal diffuser made of PMMA plastic with inner longitudinal prisms produces a uniform, homogeneous appearance with ceiling brightening. Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

| | |
|-------------------------------|--|
| Order number | 19130006090 |
| EAN number | 4020863413331 |
| Commodity code | 94051190 |
| Certification mark | IP 20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE |
| Impact resistance (IK rating) | IK03 (10°C bis 30°C) |
| Ambient temperatur | ta 10°C to 30°C |
| Special properties | Ready for IoT |
| Warranty period | 5 years |
| State funding programs | BEG - Federal funding for efficient buildings (valid only for Germany) |

ELECTRICAL ENGINEERING

| | |
|--------------------------------------|--|
| Controller | Electronic driver DALI2 (1 pcs.) |
| System output | 64W |
| Mains voltage | 230V/50Hz |
| Circuit breakers (inrush current) | 13 pieces/B10, 24 pieces/B16, 25 pieces/C10, 40 pieces/C16 |
| Energy efficiency class/light source | C |

LIGHTING TECHNOLOGY

| | |
|------------------------------------|--|
| Placement | LED, Colour rendering/Light colour CRI ≥ 80 / 3000K |
| Colour tolerance (MacAdam) | 3SDCM |
| Photobiological safety (Luminaire) | RG1 |
| Nominal luminous flux | 9490lm |
| LED service life | 50000h L80/B10 (Tq 30°C) |
| Luminaire luminous efficiency | 148lm/W |
| Beam angle | 130° (C0) / 110° (C90) |
| UGR lat./long. | 26.2 / 24.7 |

MECHANICS


| | |
|------------------------|--|
| Housing colour | traffic white RAL 9016 |
| Dimensions (LxWxH/DxH) | 1531mm x 63mm x 54mm |
| Weight (net) | 2kg |
| Type of installation | Mounting rail system installation, Light structure |

Dimensions

| | | |
|---|---------|--------|
| L | 1531 mm | Length |
| B | 63 mm | Width |
| H | 54 mm | Height |

DEEP-LINK

<https://www.regiolux.de/en/article/19130006090>



| | |
|----------------|-----------------|
| Reference | LED 10000lm 830 |
| ηLB | 100 % |
| Φ ↓/↑ | 84 % / 16 % |
| UGR lat./long. | 26.2 / 24.7 |

