

Variable device mount - Opal diffuser - direct/indirect distribution - visually continuous

Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with integrated side lever catches for rapid fitting in the mounting rail. LED unit in housing length for a continuous effect light run Variable position on the support rail. Housing colour traffic white RAL 9016; Direct/indirect light distribution, opal diffuser made of PMMA plastic with inner longitudinal prisms produces a uniform, homogeneous appearance with ceiling brightening. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 3-pin, quick-fit plug connector in the light run with free phase pre-selection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19135004040
EAN number	4020863413430
Commodity code	94051190
Certification mark	IP 20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (10°C bis 30°C)
Ambient temperatur	ta 10°C to 30°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	64W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	10 pieces/B10, 16 pieces/B16, 10 pieces/C10, 16 pieces/C16
Energy efficiency class/light source	B

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	10226lm
LED service life	50000h L80/B10 (Tq 30°C)
Luminaire luminous efficiency	160lm/W
Beam angle	130° (C0) / 110° (C90)
UGR lat./long.	26.5 / 25.0

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxDxH)	1531mm x 63mm x 54mm
Weight (net)	2.1kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	1531 mm	Length
B	63 mm	Width
H	54 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19135004040>



Reference	LED 10000lm 840
ηLB	100 %
Φ ↓/↑	84 % / 16 %
UGR lat./long.	26.5 / 25.0

