

Device mount - Satin-finish diffuser with inner longitudinal prism system - direct/indirect narrow/wide distribution - visually continuous

Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with integrated side lever catches for rapid fitting in the mounting rail. LED unit in housing length for an optically seamless light run. Housing colour black RAL 9005; Direct/indirect wide/narrow beam light distribution, the lightly satin-finished diffuser made of PMMA plastic with inner longitudinal prisms produces a uniform, homogeneous appearance with ceiling brightening. Continuous light run design. Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19150006064
EAN number	4020863414093
Commodity code	94051190
Certification mark	IP 20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (10°C bis 40°C)
Ambient temperatur	ta 10°C to 40°C
Special properties	Ready for IoT
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver DALI2 (1 pcs.)
System output	26W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	13 pieces/B10, 21 pieces/B16, 21 pieces/C10, 35 pieces/C16
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	4034lm
LED service life	50000h L80/B10 (Tq 40°C)
Luminaire luminous efficiency	158lm/W
Beam angle	45° (C0) / 100° (C90)
UGR lat./long.	21.6 / 21.6

MECHANICS


Housing colour	black RAL 9005
Dimensions (LxWxH/DxH)	1531mm x 63mm x 54mm
Weight (net)	2kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	1531 mm	Length
B	63 mm	Width
H	54 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19150006064>



Reference	LED 5000lm 830
ηLB	100 %
Φ ↓/↑	90 % / 10 %
UGR lat./long.	21.6 / 21.6

