

Device mount - Individual.Lens.Optic - direct double asymmetrical distribution - visually continuous

Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Housing colour silver grey/white aluminium RAL 9006; Direct double asymmetrical light distribution using the Individual.Lens.Optic made of PMMA plastic. The single lens optics ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The inner rhythm of the 3-row single lens arrangement and the overriding device mount are perfectly in tune to guarantee a homogeneous appearance in the object. Electrical connection by means of a fixed, 3-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19460004085
EAN number	4020863396573
Commodity code	94051190
Certification mark	IP 20, Protection class I, VDU 65°<3000, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (-20°C bis 45°C)
Ambient temperatur	ta -20°C to 45°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	26W
Mains voltage	230V/50Hz
Energy efficiency class/light source	E

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	4122lm
LED service life	50000h L80/B10 (Tq 45°C)
Luminaire luminous efficiency	160lm/W
Beam angle	70° (C0) / 90 ° (C90)
UGR lat./long.	17.9 / 16.7

MECHANICS


Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxH/DxH)	1531mm x 55mm x 37mm
Weight (net)	1.9kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	1531 mm	Length
B	55 mm	Width
H	37 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19460004085>



Reference	LED 4000lm 830
ηLB	100 %
Φ ↓/↑	99 % / 1 %
UGR lat./long.	17.9 / 16.7
VDU	65° < 3000cd/m²

