

Device mount - Individual.Lens.Optic frosted - direct/indirect diffuse distribution - visually continuous

Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated pressure locks. Housing colour traffic white RAL 9016; Direct/indirect light distribution, diffuse light beam distribution using the Individual.Lens.Optic made of frosted PMMA plastic. The single lens optics ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The inner rhythm of the 3-row single lens arrangement and the overriding device mount are perfectly in tune to guarantee a homogeneous appearance in the object. Electrical connection by means of a fixed, 3-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. The device mount can be adjusted variably in steps with a multi-lumen driver (default setting: maximum lumen output). They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19470004240
EAN number	4020863395781
Commodity code	94051190
Certification mark	IP 20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (-20°C bis 30°C)
Ambient temperatur	ta -20°C to 30°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING


Controller	Electronic multi-lumen driver, 16-steps (1 pcs.)
System output	53W-30W
Mains voltage	230V/50Hz
Energy efficiency class/light source	D

LIGHTING TECHNOLOGY



Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 6500K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux/switching steps (EDM)	7400lm/53W, 7200lm/52W, 7000lm/50W, 6800lm/48W, 6600lm/47W, 6400lm/45W, 6200lm/44W, 6000lm/42W, 5800lm/41W, 5600lm/39W, 5400lm/37W, 5200lm/36W, 5100lm/34W, 4900lm/33W, 4700lm/31W, 4500lm/30W
LED service life	50000h L80/B10 (Tq 30°C)
Luminaire luminous efficiency	151lm/W-139lm/W
Beam angle	115° (C0) / 110° (C90)
UGR lat./long.	26.4 / 25.8 (53W)

DEEP-LINK

<https://www.regiolux.de/en/article/19470004240>



Reference	LED 7400lm/53W 865
η_{LB}	100 %
$\Phi_{\downarrow/\uparrow}$	90 % / 10 %
UGR lat./long.	26.4 / 25.8



MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxDxH)	1531mm x 55mm x 37mm
Weight (net)	1.9kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	1531 mm	Length
B	55 mm	Width
H	37 mm	Height