

Variable device mount - Individual.Lens.Optic - direct asymmetrical distribution - visually continuous

Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Can be used in the track on the left or right, and positioned variably. Housing colour traffic white RAL 9016; Direct asymmetric light distribution using the Individual.Lens.Optic made of PMMA plastic. The single lens optics ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The inner rhythm of the 3-row single lens arrangement and the overriding device mount are perfectly in tune to guarantee a homogeneous appearance in the object. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 3-pin, quick-fit plug connector in the light run with free phase pre-selection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19455004110
EAN number	4020863400560
Commodity code	94051190
Certification mark	IP 20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (-20°C bis 25°C)
Ambient temperatur	ta -20°C to 25°C
Warranty period	5 years

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	70W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	10 pieces/B10, 16 pieces/B16, 10 pieces/C10, 16 pieces/C16
Energy efficiency class/light source	E

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	9413lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	135lm/W
Beam angle	20°
UGR lat./long.	18.6 / 21.9

MECHANICS



Housing colour	traffic white RAL 9016
Dimensions (LxWxDxH)	1531mm x 55mm x 37mm
Weight (net)	2kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	1531 mm	Length
B	55 mm	Width
H	37 mm	Height

DEEP-LINK

<https://www.regiolum.de/en/article/19455004110>



Reference	LED 10000lm 830
ηLB	100 %
Φ ↓/↑	98 % / 2 %
UGR lat./long.	18.6 / 21.9

