

## Mounting rail - Outfeed 7-pin

Torsion-resistant support rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal support rail suitable for light runs of all protection classes IP20 to IP64; Housing colour black RAL 9005; Heat-resistant, through-wiring with individual conductors installed in the factory. Including 2 current taps for electrical connection of the device mounts, in module 750. 1 pre-scored knock-out at the top allows a direct feed via the mounting rail. Outfeed takes place without tools via plug-type connection terminals for the connection of flexible or rigid feed cables. Cover cap for start of light run is included in the scope of supply. for SRT Mounting rail for outfeed or infeed against the direction of running

## CHARACTERISTICS

Order number	19200080104
EAN number	4020863423712
Commodity code	94059900
Certification mark	IP 20/40, Protection class I, Indoor, CE

## ELECTRICAL ENGINEERING

Wiring	7x2.5mm <sup>2</sup>
--------	----------------------

## MECHANICS

Housing colour	black RAL 9005
Dimensions (LxWxH/DxH)	1535mm x 63mm x 46mm
Weight (net)	1.65kg
Type of installation	Mounting rail system installation, Light structure

## Dimensions

L	1535 mm	Length
B	63 mm	Width
H	46 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19200080104>

