

universal-mounting rail - Universal mounting rail, flexible, current taps every 767.5 mm, for device mount module /750, /1500 and /2250

Torsion-resistant support rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal support rail suitable for light runs of all protection classes IP20 to IP64; Housing colour silver grey/white aluminium RAL 9006; Heat-resistant, through-wiring with individual conductors installed in the factory. Including 4 current taps for electrical connection of the device mounts, in module 750. With push connection at the end of the mounting rail for the fast electrical connection of further mounting rails. 2 pre-scored knock-outs at the top allow a direct feed via the mounting rail. Feed adapter and optional mounting rail including outfeed required. Please order assembly accessories as well as rail end pieces and connectors separately.

## CHARACTERISTICS

Order number	19273004105
EAN number	4020863383580
Commodity code	94059900
Certification mark	IP 20/40/54/64, Protection class I, Indoor, CE

## ELECTRICAL ENGINEERING

Wiring	5x2.5 / 6x1.5mm <sup>2</sup>
--------	------------------------------

## MECHANICS

Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxH/DxH)	3070mm x 63mm x 46mm
Weight (net)	3.725kg
Type of installation	Mounting rail system installation, Light structure

## Dimensions

L	3070 mm	Length
B	63 mm	Width
H	46 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19273004105>

