

IP 64 variable device mount - Central.Line.Optic - direct wide distribution - visually continuous

Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Variable position on the support rail. Housing colour traffic white RAL 9016; Direct, wide-beam light distribution using the Central.Line.Optic made of PMMA plastic. The lens optics have a transparent seal, ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The compact 1-row arrangement of the lenses ensures that the dots merge into a line with a homogeneous appearance in the object. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 5-pin, quick-fit plug connector in the light run with free phase pre-selection; With 3h emergency lighting battery; Luminaire status by visible status LED in luminaire (NL-B3); Luminous flux in emergency light mode 927 lm. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

Order number	19517027250
EAN number	4020863445363
Commodity code	94051190
Certification mark	IP 64, Protection class I, F, D, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (5°C bis 25°C)
Ambient temperatur	ta 5°C to 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

## ELECTRICAL ENGINEERING

Controller	Electronic driver 3h emergency lighting (1 pcs.)
System output	132W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	7 pieces/B10, 12 pieces/B16, 12 pieces/C10, 20 pieces/C16
Energy efficiency class/light source	C

## LIGHTING TECHNOLOGY


Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	21418lm
Nominal luminous flux-emergency lighting mode	927lm
LED service life	50000h L80/B10 (Tq 25°C), 70000h L80/B50 (Tq 25°C)
Luminaire luminous efficiency	163lm/W
Beam angle	95° (C0) / 95° (C90)
UGR lat./long.	24.6 / 26.1

## MECHANICS



Housing colour	traffic white RAL 9016
Dimensions (LxWxDxH)	2299mm x 55mm x 37mm
Weight (net)	2.55kg
Type of installation	Mounting rail system installation, Light structure

## DEEP-LINK

<https://www.regiolum.de/en/article/19517027250>



Reference	LED 21000lm 840
ηLB	100 %
Φ ↓/↑	98 % / 2 %
UGR lat./long.	24.6 / 26.1



## Dimensions

---

L	2299 mm	Length
B	55 mm	Width
H	37 mm	Height

---