

IP 64 variable device mount - Central.Line.Optic high performance - direct, narrow distribution - visually continuous

Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Variable position on the support rail. Housing colour traffic white RAL 9016; Direct, narrow-beam light distribution using the Central.Line.Optic HP made of PMMA plastic. High Performance (HP) version with peak values in light current and luminaire efficiency. Suitable for higher ambient temperatures. Features an extra long LED life. The lens optics have a transparent seal, ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The compact 1-row arrangement of the lenses ensures that the dots merge into a line with a homogeneous appearance in the object. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 3-pin, quick-fit plug connector in the light run with free phase pre-selection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19527024390
EAN number	4020863440658
Commodity code	94051190
Certification mark	IP 64, Protection class I, ENEC10 VDE, F, D, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (-20°C bis 40°C)
Ambient temperatur	ta -20°C to 40°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	73W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	13 pieces/B10, 21 pieces/B16, 22 pieces/C10, 36 pieces/C16
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 6500K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	12351lm
LED service life	70000h L80/B10 (Tq 40°C), 100000h L80/B50 (Tq 35°C)
Luminaire luminous efficiency	169lm/W
Beam angle	25° (C0) / 100° (C90)
UGR lat./long.	17.7 / 23.0

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	2299mm x 55mm x 37mm
Weight (net)	2.3kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	2299 mm	Length
B	55 mm	Width
H	37 mm	Height

DEEP-LINK

<https://www.regiolum.de/en/article/19527024390>



Reference	LED 13000lm 865
ηLB	100 %
Φ ↓/↑	98 % / 2 %
UGR lat./long.	17.7 / 23.0

