SRGSVOB /1500 LED 4000 865 • vw RAL 9016 • DALI2 • 19417006150



IP 64 variable device mount - Individual.Lens.Optic - direct wide distribution - visually continuous

Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Variable position on the support rail. Housing colour traffic white RAL 9016; Direct, wide-beam light distribution using individual LED lens optic made of PMMA plastic. The single lens optics has a transparent seal, ensures absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The inner rhythm of the 3-row single lens arrangement and the overriding device mount are perfectly in tune to guarantee a homogeneous appearance in the object. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 5-pin, quick-fit plug connector in the light run with free phase pre-selection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

DEEP-LINK

CHARACTERISTICS

Order number	19417006150
EAN number	4020863411214
Commodity code	94051190
Certification mark	IP 64, Protection class I, VDU 65°<3000, ENEC10 VDE, F, D, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (-20°C bis 45°C)
Ambient temperatur	ta -20°C to 45°C
Special properties	Ready for IoT
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver DALI2 (1 pcs.)	
System output	26W	
Mains voltage	230V/50Hz	
Circuit breakers (inrush current)	20 pieces/B10, 32 pieces/B16, 33 pieces/C10, 53 pieces/C16	
Energy efficiency class/light source	D	


LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour	
	CRI ≥ 80 / 6500K	
Colour tolerance (MacAdam)	3SDCM	
Photobiological safety (Luminaire)	RG1	
Nominal luminous flux	4227lm	
LED service life	50000h L80/B10 (Tq 45°C)	
Luminaire luminous efficiency	164lm/W	
Beam angle	95° (C0) / 95 ° (C90)	
UGR lat./long.	18.7 / 19.2	

MECHANICS

Housing colour	traffic white RAL 9016	
Dimensions (LxWxH/DxH)	1531mm x 55mm x 33mm	
Weight (net)	2kg	
Type of installation	Mounting rail system installation, Light	
	structure	

Dimensions			
L	1531 mm	Length	
В	55 mm	Width	
н	33 mm	Height	





0)(0