

IP 64 variable device mount - Individual.Lens.Optic - direct, extremely wide distribution - visually continuous

Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Variable position on the support rail. Housing colour traffic white RAL 9016; Direct, extremely wide-beam light distribution using individual LED lens optic made of PMMA plastic. The single lens optics has a transparent seal, ensures absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The inner rhythm of the 3-row single lens arrangement and the overriding device mount are perfectly in tune to guarantee a homogeneous appearance in the object. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 3-pin, quick-fit plug connector in the light run with free phase pre-selection. The device mount can be adjusted variably in steps with a multi-lumen driver (default setting: maximum lumen output). They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS


Order number	19487004220
EAN number	4020863398898
Commodity code	94051190
Certification mark	IP 64, Protection class I, ENEC10 VDE, F, D, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (-20°C bis 30°C)
Ambient temperatur	ta -20°C to 30°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

## ELECTRICAL ENGINEERING



Controller	Electronic multi-lumen driver, 16-steps (1 pcs.)
System output	53W-30W
Mains voltage	230V/50Hz
Energy efficiency class/light source	D

## DEEP-LINK

<https://www.regiolum.de/en/article/19487004220>



Reference	LED 8200lm/53W 840
$\eta_{LB}$	100 %
$\Phi \downarrow/\uparrow$	98 % / 2 %
UGR lat./long.	23.2 / 23.5



**LIGHTING TECHNOLOGY**

<b>Placement</b>	LED, Colour rendering/Light colour CRI $\geq 80$ / 4000K
<b>Colour tolerance (MacAdam)</b>	3SDCM
<b>Photobiological safety (Luminaire)</b>	RG1
<b>Nominal luminous flux/switching steps (EDM)</b>	8200lm/53W, 8000lm/52W, 7800lm/50W, 7600lm/48W, 7400lm/47W, 7100lm/45W, 6900lm/44W, 6700lm/42W, 6500lm/41W, 6300lm/39W, 6100lm/37W, 5800lm/36W, 5600lm/34W, 5400lm/33W, 5200lm/31W, 5000lm/30W
<b>LED service life</b>	50000h L80/B10 (Tq 30°C)
<b>Luminaire luminous efficiency</b>	168lm/W-155lm/W
<b>Beam angle</b>	105° (C0) / 105° (C90)
<b>UGR lat./long.</b>	23.2 / 23.5 (53W)

**MECHANICS**

<b>Housing colour</b>	traffic white RAL 9016
<b>Dimensions (LxWxH/DxH)</b>	1531mm x 55mm x 37mm
<b>Weight (net)</b>	2kg
<b>Type of installation</b>	Mounting rail system installation, Light structure

**Dimensions**

<b>L</b>	1531 mm	Length
<b>B</b>	55 mm	Width
<b>H</b>	37 mm	Height