

IP 54 variable Device mount functional module netlife light management

Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantee good corrosion protection; tool-free attachment with integrated rotary catches for rapid fitting in the support rail. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP54. For integrating sensor technology and the control unit into the light run; can be positioned variably in the support rail. Housing colour traffic white RAL 9016; Electrical connection by means of a 0.7m connection cable for variable device mount positioning in the light run with freely positionable phases. Light Control: netlife easy15; Regiolux Classification: netlife easy; Control signal: DALI2-broadcast; Supported DALI parts: 201(DT0), 207(DT6), 208(DT7); DALI-output nom.: 80mA; Communication: Wired; Sensor technology: PIR - passive infrared; Installation height (min/max): 2m to 10m; Monitoring area: max. D=34m; Remote control: 84506028100; Optional remote control: 84506021200 +App; App name: B.E.G. One; System extension: easy19; Application: Office, Meeting rooms, Corridors, Industry, Classrooms, Secondary rooms, Logistics centres, Garages; Function: Daylight control, Manual dimming, Motion detection, Corridor function, presence detection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. netlife easy system; straightforward in-house project engineering; easy installation; preset functions; simple commissioning via remote control, app, DIP switch, rotary knob, etc.

CHARACTERISTICS

Order number	19152700150
EAN number	4020863421480
Commodity code	90328900
Certification mark	IP 54, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Special properties	Advanced Services

ELECTRICAL ENGINEERING

Controller	easy15
Mains voltage	230V/50Hz

MECHANICS



Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	765mm x 110mm x 107mm
Weight (net)	0.9kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	765 mm	Length
B	110 mm	Width
H	107 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19152700150>



LC SYSTEM

CHARACTERISTICS

Regiolux Classification	netlife easy
Control signal	DALI2-broadcast
Supported DALI parts	201(DT0), 207(DT6), 208(DT7)
DALI-output nom.	80mA
Communication	Wired
Sensor technology	PIR - passive infrared
Installation height (min/max)	2m to 10m
Remote control	84506028100
Optional remote control	84506021200 +App
App name	B.E.G. One
System extension	easy19
Application	Office, Meeting rooms, Corridors, Industry, Classrooms, Secondary rooms, Logistics centres, Garages
Function	Daylight control, Manual dimming, Motion detection, Corridor function, presence detection

MONITORING AREA

Mounting Height	3m	10m
Ø max. sitting[S]	6,4m	-
Ø max. radial[R]	8m	-
Ø max. tangential[T]	24m	34m

