

IP 54 variable Device mount functional module netlife light management

Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantee good corrosion protection; tool-free attachment with integrated rotary catches for rapid fitting in the support rail. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP54. For integrating sensor technology and the control unit into the light run; can be positioned variably in the support rail. Housing colour traffic white RAL 9016; Electrical connection by means of a 0.7m connection cable for variable device mount positioning in the light run with freely positionable phases. Light Control: netlife flex37; Regiolux Classification: netlife flex; Control signal: Radio; Communication: Bluetooth; Sensor technology: PIR - passive infrared; Installation height (min/max): 5m to 16m; Monitoring area: max. 30m x 19m; App name: Casambi; System compatibility: flex10; flex10X; flex10L; flex37; flex39; Note: compatible with Casambi; System extension: flex37, flex39; Application: Industry, Logistics centres; Function: Motion detection, Corridor function, Guided Light, Daylight control. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. netlife flex system; in-house project engineering or by customer; easy installation, extended functions and variable settings; easy commissioning per app, extended interconnectabilities

## CHARACTERISTICS

Order number	19152700370
EAN number	4020863421572
Commodity code	90328900
Certification mark	IP 54, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Special properties	Advanced Services

## ELECTRICAL ENGINEERING

Controller	flex37
Mains voltage	230V/50Hz

## MECHANICS



Housing colour	traffic white RAL 9016
Dimensions (LxWxDxH)	765mm x 110mm x 99mm
Weight (net)	1.2kg
Type of installation	Mounting rail system installation, Light structure

## Dimensions

L	765 mm	Length
B	110 mm	Width
H	99 mm	Height

## DEEP-LINK


<https://www.regiolux.de/en/article/19152700370>



## LC SYSTEM

### CHARACTERISTICS

Regiolux Classification	netlife flex
Control signal	Radio
Communication	Bluetooth
Sensor technology	PIR - passive infrared
Installation height (min/max)	5m to 16m
App name	Casambi
System compatibility	flex10; flex10X; flex10L; flex37; flex39
Note	compatible with Casambi
System extension	flex37, flex39
Application	Industry, Logistics centres
Function	Motion detection, Corridor function, Guided Light, Daylight control



### MONITORING AREA

Mounting Height	14m	16m
Ø max. sitting[S]	-	-
Ø max. radial[R]	30x19m	30x19m
Ø max. tangential[T]	30x19m	30x19m

