

IP 54 Variable LED device mount functional module for safe emergency luminaire - LED single-lens optics - direct asymmetrical distribution

Device mounts, made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantee good corrosion protection; attachment without tools with integrated rotary catches for rapid fitting in the support rail. Variable position on the support rail. Housing colour traffic white RAL 9016; Direct double asymmetrical and bright light distribution using single lens can be turned through 90°. Electrical connection by means of a 0.7m connection cable for variable positioning of the device mount with a 5-pin, quick-fit plug connector in the light run and free phase pre-selection; With 3h emergency lighting battery; with automatic self test function; Luminaire status via visible, two-color status LED in the luminaire (NL-B3S); Luminous flux in emergency light mode 197 lm. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

Order number	19072002000
EAN number	4020863420544
Commodity code	94051190
Certification mark	IP 54, Protection class I, F, D, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (5°C bis 25°C)
Ambient temperatur	ta 5°C to 25°C
Warranty period	5 years

## ELECTRICAL ENGINEERING

Controller	Electronic driver 3h emergency lighting with automatic self-test (1 pcs.)
System output	4W
Mains voltage	230V/50Hz

## LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 70 / 6000K
Colour tolerance (MacAdam)	7SDCM
Photobiological safety (Luminaire)	RG2
Nominal luminous flux	197lm
Nominal luminous flux-emergency lighting mode	197lm
Luminaire luminous efficiency	49lm/W
Beam angle	45° (C0) / 125° (C90)
UGR lat./long.	29.8 / 35.2

## MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	765mm x 55mm x 35mm
Weight (net)	0.85kg
Swivel and turn area (x/y/z)	0° / 0° / 90°
Type of installation	Mounting rail system installation, Light structure

## Dimensions

L	765 mm	Length
B	55 mm	Width
H	35 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19072002000>



Reference	LED 200lm 760
ηLB	100 %
Φ ↓/↑	93 % / 7 %
UGR lat./long.	29.8 / 35.2

