

## Mounting rail - Outfeed 11-pin

Mounting rail made of profiled, torsion-resistant sheet steel, pre-galvanised; blank cover and rail connector for SRT quick-fit mounting system module length /500; Housing colour traffic white RAL 9016; Outfeed by means of plug and cable with 2-fold plug-type connection terminals 11x1.5-2.5mm<sup>2</sup>, suitable for the connection of flexible and rigid supply cables as central feed with feed adapter SRTA-7E;. Cover cap for start of light run is included in the scope of supply. for SRT

## CHARACTERISTICS

|                    |  |
|--------------------|--|
| Order number       | 19200015100                                    |
| EAN number         | 4020863388202                                  |
| Commodity code     | 94059900                                       |
| Certification mark | IP 20/40/54/64, Protection class I, Indoor, CE |

## MECHANICS

|                        |  |
|------------------------|--|
| Housing colour         | traffic white RAL 9016                             |
| Dimensions (LxWxH/DxH) | 500mm x 63mm x 46mm                                |
| Weight (net)           | 0.81kg   |
| Type of installation   | Mounting rail system installation, Light structure |

## Dimensions

|   |        |        |
|---|--------|--------|
| L | 500 mm | Length |
| B | 63 mm  | Width  |
| H | 46 mm  | Height |

## DEEP-LINK

<https://www.regiolux.de/en/article/19200015100>

