

Recessed luminaire - Satin-finished diffuser - direct distribution

Sheet steel housing suitable for ceilings with visible T rails, concealed symmetrical rail constructions and cut-out ceilings; protection rating refers to visible luminaire surface; Housing colour traffic white RAL 9016; Direct diffuse light distribution using diffuse-radiation frosted diffuser made of acrylic glass with naturally anodised aluminium frame, neutral white light colour (840) with very good colour consistency and high colour rendering Ra>80. Electrical connection via 3-pole connection terminal with plug-in contacts.; With changeover converter for emergency lighting operation on request. An extractor is included for prismatic and frosted panes to remove the sealing frame. UBM universal mounting brackets for concealed symmetrical rail constructions or recessed ceilings and SCT CLIPS locking clips for ceilings with visible T rails; please order separately. A vacuum lifting pad SH 55 is needed to draw off the sealing frame.

## CHARACTERISTICS

Order number	72512034110
EAN number	4020863289936
Commodity code	94051190
Certification mark	IP 54, Protection class I, F, HACCP DIN10500/Food/IFS/BRC, Indoor, CE
Impact resistance (IK rating)	IK03
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

## ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	29W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	19 pieces/B10, 30 pieces/B16, 31 pieces/C10, 50 pieces/C16
Energy efficiency class/light source	C

## LIGHTING TECHNOLOGY


Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG0
Nominal luminous flux	4839lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	169lm/W
UGR lat./long.	20.9 / 21.4

## MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1247mm x 309mm x 89mm
Depth	82mm
Ceiling system	ceilings with visible T-rails [s-TS] (312.5x1250 mm), Concealed symmetrical rail construction [VS] (312.5x1250 mm), cut-out ceilings [AD]
Ceiling cut-out (LxW/D)	1185mm x 285mm
Installation depth	150mm [AD]; 250mm [s-TS]; 150mm [s-TS] min; 150mm [VS]
Weight (net)	6.71kg
Type of installation	Recessed mounting, Ceiling installation individual mounting

## DEEP-LINK

<https://www.regiolum.de/en/article/72512034110>



Reference	LED 4700lm 840
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	20.9 / 21.4



## Dimensions

<b>L</b>	1247 mm	Length
<b>B</b>	309 mm	Width
<b>H</b>	89 mm	Height
<b>T</b>	82 mm	Depth
<b>DA(L)</b>	1185 mm	Cutting dimension length
<b>DA(B)</b>	285 mm	Cutting dimension width
<b>DS min</b>	15 mm	Ceiling thickness minimum
<b>DS max</b>	40 mm	Ceiling thickness maximum
<b>Et(min)</b>	150 mm	Ceiling distance minimum - minimum dimension (visible T-rail)
<b>Et(AD)</b>	150 mm	Ceiling distance minimum (cut-out ceiling)
<b>Et(TS)</b>	250 mm	Ceiling distance minimum - recommended (visible T-rail)
<b>Et(VS)</b>	150 mm	Ceiling distance minimum (concealed symmetrical)
<b>MLTS1</b>	1250 mm	Module dimension length (visible T-rail)
<b>MLTS_1/2</b>	1250	Module dimension length (visible T-rail) 1/2
<b>MLVS</b>	1250 mm	Module dimension length (concealed symmetrical)
<b>MBTS1</b>	312.5 mm	Module dimension width (visible T-rail)
<b>MBTS_1/2</b>	312.5	Module dimension width (visible T-rail) 1/2
<b>MBVS</b>	312.5 mm	Module dimension width (concealed symmetrical)