

Track

Three-phase track made of extruded aluminium profile, max. 16 A incl. DALI control lines, rail can be shortened to any length. Housing colour white RAL 9010; Suitable for luminaires with a 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac.

CHARACTERISTICS

Order number	37644110100
EAN number	4020863468591
Commodity code	94059900
Certification mark	IP 20, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Mains voltage	230V/50Hz
---------------	-----------

MECHANICS

Housing colour	white RAL 9010
Dimensions (LxWxDxH)	1000mm x 31.4mm x 37.8mm
Installation depth	0mm [VA]
Weight (net)	1.1kg
Type of installation	Track mounting, Light structure, Pendant light strip mounting, Ceiling-mounted trunking installation

Dimensions

L	1000 mm	Length
B	31.4 mm	Width
H	37.8 mm	Height
Et(VA)	0 mm	Ceiling distance minimum (concealed asymmetrical)
Et(PD)	0 mm	Ceiling distance minimum (panel ceiling)

DEEP-LINK

<https://www.regiolux.de/en/article/37644110100>

