

Track

Three-phase track made of extruded aluminium profile, max. 16 A incl. DALI control lines, rail can be shortened to any length. Housing colour silver grey/white aluminium RAL 9006; Suitable for luminaires with a 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac.

CHARACTERISTICS

Order number	37644410105
EAN number	4020863468706
Commodity code	94059900
Certification mark	IP 20, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Mains voltage	230V/50Hz
---------------	-----------

MECHANICS

Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxH/DxH)	4000mm x 31.4mm x 37.8mm
Installation depth	0mm [VA]
Weight (net)	4.5kg
Type of installation	Track mounting, Light structure, Pendant light strip mounting, Ceiling-mounted trunking installation

Dimensions

L	4000 mm	Length
B	31.4 mm	Width
H	37.8 mm	Height
Et(VA)	0 mm	Ceiling distance minimum (concealed asymmetrical)
Et(PD)	0 mm	Ceiling distance minimum (panel ceiling)

DEEP-LINK

<https://www.regiolux.de/en/article/37644410105>

