

## Track

Three-phase track made of extruded aluminium profile, max. 16 A incl. DALI control lines, rail can be shortened to any length. Housing colour white RAL 9010; Suitable for luminaires with a 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac.

## CHARACTERISTICS

Order number	37644410100
EAN number	4020863468683
Commodity code	94059900
Certification mark	IP 20, Protection class I, Indoor, CE

## ELECTRICAL ENGINEERING

Mains voltage	230V/50Hz
---------------	-----------

## MECHANICS

Housing colour	white RAL 9010
Dimensions (LxWxH/DxH)	4000mm x 31.4mm x 37.8mm
Installation depth	0mm [VA]
Weight (net)	4.5kg
Type of installation	Track mounting, Light structure, Pendant light strip mounting, Ceiling-mounted trunking installation

## Dimensions

L	4000 mm	Length
B	31.4 mm	Width
H	37.8 mm	Height
Et(VA)	0 mm	Ceiling distance minimum (concealed asymmetrical)
Et(PD)	0 mm	Ceiling distance minimum (panel ceiling)

## DEEP-LINK

<https://www.regiolux.de/en/article/37644410100>

